



RCP NOTES

1) ALL BULBS TO BE LED 2700K TEMPERATURE
2) CONTRACTOR TO SUBMIT ALL FIXTURES FOR APPROVAL PRIOR TO PURCHASE

3) USB OUTLETS TO BE DUPLEX OUTLETS WITH TWO USB PORTS

4) CAN LIGHTS IN SLOPED CEILING TO BE ADJUSTABLE ANGLE AND AIR SEALED. PROVIDE INSULATED COVER OVER LIGHT TO SHIELD HEAT

5) CAN LIGHTS IN WET AREAS TO BE WATER TIGHT

RCP LEGEND

220V DUPLEX OUTLET @ 1'-6"

DUPLEX OUTLET @ 1'-6"

DUPLEX OUTLET @ 4'-0"

GFCI OUTLET @ 4'-0"

J

\$\text{SWITCH ON TIMER}\$\\ \frac{\\$}{3} \quad \text{THREE WAY SWITCH} \\ \frac{\\$}{4} \quad \text{FOUR WAY SWITCH} \end{array}

FAN/LIGHT COMBO

RECESSED CAN LIGHT

SINGLE POLE SWITCH

JAMB SWITCH

DIMMER SWITCH

JUNCTION BOX

SEMI FLUSH WALL MOUNTED LIGHT

S SMOKE DETECTOR

2 LI
A215 1/

2 LEVEL 6
A215 1/4" = 1'-0"

with all laws and regulations of the District of Columbia I have personally prepared, of directly supervised the development of the architectural designs included in this application.

No. Description Date

This drawing is an instrument of service and shall remain the property of the Architects and shall not be reproduced, published or used in any way without the permission of Lee Design Studios LLC.

SHEET TITLE

SIXTH FLOOR AND RCP

SHEET TITLE

SHEET NUMBER

11/2/20